

# Solar Flashings for tile and slate roofs

## Solardek™

The speciality Flashing for solar thermal installations

The purpose designed SolarDek™ provides the safest, most efficient method of flashing solar thermal pipes and cables on tile and slate roofs.

SolarDek™ features the Nu Lead base which will not stain or corrode the roof, together with long life Dektite® EPDM or grey silicone cone ideally suited to solar thermal pipe sizes.



## Solardek™

- Grey high temperature seal
- Complete weather proofing for all solar thermal pipes and cables
- Safe protected Nu Lead® apron
- Purpose made durable solution as required by MCS

Pipe External	Roof Pitch	Base Size	Base Type	Code		List Price
				Black EPDM	Black EPDM	
0 35mm	0 45°	490 x 410mm	Nu Lead	DNLS100B		58.22
0 35mm	0 45°	450 x 600mm	Aluminium	SDA MINI		35.87

Pipe External	Roof Pitch	Base Size	Base Type	Code		List Price
				Grey Silicone	Grey Silicone	
0 35mm	0 45°	490 x 410mm	Nu Lead	DNLS200G		58.22
0 35mm x 2	0 45°	490 x 410mm	Nu Lead	DNLS200MPG		66.95

## Dektite® Multicable Solar Flashing

The speciality flashing for solar PV cables on tile or slate roofs

Allows up to 10 cables to be taken effectively through any tile or slate roof. Avoids risk of damage or pressure on cables by isolating from tiles or slates and provides a complete weatherproof seal. Black EPDM cone, features Nu Lead® acrylic coated lead base.



## Dektite® Multicable

- Black EPDM High UV resistant cone
- Available with Aluminium or Nu Lead® base
- Weather seals and protects up to 10 cables
- Purpose made durable solution as required by MCS

Cable External	Roof Pitch	Base Size	Base Type	Code		List Price
				Black EPDM	Black EPDM	
4 8mm	Any	490 x 410mm	Nu Lead	DNLS10MB		58.22
4 8mm	Any	450 x 600mm	Aluminium	SDA 10MB		38.58

# Solar Flashings for metal roofs

## Dektite® Premium

Perfect for Flashing Pipes and Cables on Metal Roofs

The multi application flashing in a highly durable EPDM or silicone, edged with a flexible aluminium band, flashes pipes and cables on metal roofs. The square base fits most roof profiles.



### Dektite® Premium DFE 100/200

- ✓ For solar pipe or up to 3 cables
- ✓ Suits most roof profiles
- ✓ Available in black and grey EPDM or red silicone

### Dektite® Premium DFE 101/201

- ✓ Versatile flashing, accommodates up to 5 penetrations
- ✓ Suitable for pipes and/or cables
- ✓ High UV resistance

### Dektite® Premium Multicable DFE 101BM

- ✓ Protects up to 12 cables and weatherproofs entry to any metal roof
- ✓ Purpose made durable solution as required by MCS
- ✓ Suits most roof profiles

Pipe External	Cable External	Roof Pitch	Base Size	Code		List Price		Code		List Price	
				Red Silicone	Red Silicone	Grey EPDM	Grey EPDM	Black EPDM	Black EPDM		
0 35mm	4 8mm	0 45°	100 x 100mm	DFE200RES	10.04	DFE100GS	8.72	DFE100BS	7.72		
5 55mm	4 8mm	0 45°	139 x 139mm	DFE201RES	13.30	DFE101GS	10.93	DFE101BS	9.67		
N/A	4 8mm	Any	139 x 139mm	N/A	N/A	N/A	N/A	DFE101BM	10.99		